



**Eaton Industrial Hose**  
**EHP500 - PETROLEUM / OIL SUCTION & DISCHARGE**

## Overview & Features

Oil and petroleum suction and discharge hose

### Features

- 150 psi operating pressure
- -31F to 158F temperature rating
- NBR tube and cover
- High tensile synthetic reinforcement with single helical wire
- 3:1 Safety Factor
- 50% aromatic content resistant

## Where Used



### Aerospace

**Applications:**

- Oil, petroleum and waste transfer



### Buildings

**Applications:**

- Oil, petroleum and waste transfer



### Government

**Applications:**

- Oil, petroleum and waste transfer



### Marine

**Applications:**

- Oil, petroleum and waste transfer



### Oil and gas

**Platforms:**

- Downstream: Petrochemical
- Downstream: Refining (Ethanol/Biodiesel)
- Downstream: Terminal Operations (refined gas and liquids)
- Midstream: Saddle Plants
- Midstream: Terminal Operations (unrefined gas and liquids)
- Upstream: Offshore (fixed or floater) Offloading Systems
- Upstream: Onshore Drilling Operations
- Upstream: Onshore Pump Jacks

**Applications:**

- Oil, petroleum and waste transfer



### Rail

**Applications:**

- Oil, petroleum and waste transfer



### Vehicles

**Platforms:**

- Heavy Duty On-Highway
- Medium Duty On-Highway

**Applications:**

- Oil, petroleum and waste transfer



### Water and wastewater

**Applications:**

- Oil, petroleum and waste transfer

## Value Propositions

Value Proposition Statement	Audiences		
	OEM	Distributor	End User
Completes breadth of portfolio to capitalize on core product market opportunities			
Easy identification in the toughest environments provided by dual Mylar and embossed laylines , verses competitive single layline alternatives, creating ease of replenishment and traceability			

## Tools & Collateral

---

### Catalog

[Industrial Hose Catalog North America : E-HOOV-MC003-E2](#)

[Industrial Hose Oil and Gas Exploration Catalog: E-HOOIN-88004-E](#)